

PRINZOL LUBRICANTS, INC



Product Data Sheet Rev 03/08/2017

Prinzol CSI 150 Base Stock

PRINZOL Group I base oils are highly refined premium quality paraffinic base oils. Group I base oils are solvent refined and dewaxed to perform a variety of industrial and automotive applications. Our group I base oils contain 0.03 percentages or greater quantity of sulfur and contains less than 90 percent saturates. Prinzol premium quality base oils contain a viscosity index between 80 and 120. The temperature of our group I base stock ranges from 32° Fahrenheit to 100° Fahrenheit.

PRODUCT:	PRINZOL CSI 150 Base Stock
Product Code	22-150
Viscosity cSt@40°C	482.8
Viscosity cSt@100°C	31.7
Viscosity, SUS @ 100°F	2590
Viscosity Index	96
API Gravity	25
Pour Point, °C	-6
Flash Point, °C	305
Color (ASTM-D-1500)	L 3.5
Sulfur Wt. % (ASTM-D-4294)	1.10
GC Sim Distillation (ASTM-D-2887)	
Boiling Range, °C	258
5%	387
95%	563
%Off at 371.11°C	
Noack Volatility Wt. % (ASTM-D-5800)	
Conradson Carbon Residue Wt. % (ASTM-D-4530)	0.51
Clay Gel Analysis (ASTM-D-2007)	
Asphaltenes Wt. %	<0.1
Aromatics Wt. %	36.1
Polar Cpds Wt. %	3.2
Saturates, Wt. %	60.7